

TECHNICAL DATA SHEET

AMLSAL IP44 / Aga-Led® Type A

VERSION - 13.11.2015


STANDARD LUMINAIRE

Reference	AMLSAL
Protection Class	IP44
Lighting Source	Aga-Led® Type A
Connector	Festoon on B'Light conductor 16mm ²
Dimensions	120 x 60mm
Standard Length	610 - 910 - 1210 - 1510mm
Length on measure	on request up to 2965
Nb Lighting Unit	17 LED/m
Voltage	24V
Power	17 W/m
Connecting Cable	1m standard cable 2x1.5mm ²
Fixation	FIX
End Caps	ARL + EFA

APPLICATION: Miroirs, walls



AMLSAL / AGA-LED® TYPE A - Festoon



FINISH

Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-Enameling Powder Coating RAL Color Anodising Polished Aluminium Chrome Aspect Polished Aluminium Gold Aspect Plywood

Glass Finishing

Standard	VER: Opaline Glass
On request	VERC: Clear Glass

ON REQUEST

Connecting Plug	AMS / AF
Dimming Option	1-10V, Dali, KNX <i>Ask technical departement for more information</i>

LIGHTING SOURCE

Lighting Source	Aga-Led® Type A
Ref	A10
Voltage	24V
Power	1W
Beam Angle	15°
CRI	80
Lifetime	60'000h
Working T°	-30°C ~ +55°C
Option	AGC: Anti Glare Optic




Color Temperature & Luminous Flux / Unit

CCT	2800K	4000K
Luminous Flux/Unit	40 lm	45 lm

CERTIFICAT



FIXATION : FIX



ON REQUEST : Connecting plug AMS/AF

