

## TECHNICAL DATA SHEET

### LU4SAL IP67 / Aga-Led® Type B

VERSION - 15.05.2017

#### STANDARD LUMINAIRE

Reference	LU4SAL67
Protection Class	IP67 with Silicone
Lighting Source	Aga-Led® Type B
Connector	Festoon on B'Light conductor 16mm <sup>2</sup>
Dimensions	24 x 14mm
Standard Length	330 - 670 - 1000 - 1330 - 1670 - 2000
Length on measure	on request up to 3000mm
Nb Lighting Unit	17 LED/m
Voltage	24V
Power	With B3: 16.32 W/m With B6: 20.4 W/m
Connecting Cable	One side: 50cm standard cable 2x0.75mm <sup>2</sup>
End Caps	EU4

#### FINISH

##### Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-enameling Powder Coating RAL Color Anodising

#### ON REQUEST

Fixation	FCU (Width: +4mm)
Cover	VRC: Clear Glass / VRM: Opaline Glass VSC: Clear Glass / VSM: Opaline Glass
End Caps	EU4C (For VSC/VSM Cover)
Connecting Plug	AMS / AF or AMS-E / AF-E
Dimming Option	1-10V, Dali, KNX <i>Ask technical departement for more information</i>

#### LIGHTING SOURCE

Lighting Source	Aga-Led® Type B - Generation 2	
Ref	B3	B6
Power	0.96W	1.2W
Voltage	24V	24V
Beam Angle	120°	120°
CRI	80	80
Lifetime	50'000h	
Working T°	-20°C to +45°C	
Environmental protection	Modified acrylate resin	


#### Color Temperature & Luminous Flux / Unit

	2200K	2400K	2700K	3000K	4000K
Aga-Led® B3-G2	--	97 lm	137lm	137lm	137lm
Aga-Led® B6-G2	129 lm	140 lm	166 lm	166 lm	166 lm


#### CERTIFICAT



#### LU4SAL / AGA-LED® TYPE B - Festoon




#### ON REQUEST: LU4SAL67 FIXATION




#### ON REQUEST: LU4SAL Cover

##### LU4SAL + VRC (or VRM)



##### LU4SAL + VSC (or VSM)



#### ON REQUEST: Connecting Plug

##### AF/AMS



##### AF-E/AMS-E (IP68)

