

## TECHNICAL DATA SHEET

### TLFSAL IP20 / Aga-Led® Type A

VERSION - 06.05.2016


#### STANDARD LUMINAIRE

Reference	TLFSAL
Protection Class	IP20
Lighting Source	Aga-Led® Type A
Connector	Festoon on B'Light conductor 16mm <sup>2</sup>
Dimensions	26 x 23mm
Standard Length	330 - 670 - 1000 - 1330 - 1670 - 2000mm
Length on measure	on request up to 3000mm
Nb Lighting Unit	36 LED/m
Voltage	24V
Power	36 W/m
Connecting Cable	1m standard cable 2x1.5mm <sup>2</sup>

#### APPLICATION: cornices, handrails, stairs, shelves



#### TLFSAL / AGA-LED® TYPE A - Festoon




#### FINISH

##### Color Finishing Profil

Standard	Natural Anodised Aluminium
On request	Thermo-Enameling Powder Coating RAL Color Anodising Polished Aluminium Chrome Aspect Polished Aluminium Gold Aspect

#### ON REQUEST: TLFSAL Fixation TFCEP-S



#### ON REQUEST

Fixation	TFCEP (Width: +3mm / Ht: +0.2mm) TFCEP-S (Width: +3mm / Ht: +4.5mm)
Connecting Plug	AMS / AF
Dimming Option	1-10V, Dali, KNX <i>Ask technical departement for more information</i>

#### ON REQUEST : Connecting plug AF/AMS



#### LIGHTING SOURCE

Lighting Source	Aga-Led® Type A
Ref	A10
Voltage	24V
Power	1W
Beam Angle	15°
CRI	80
Lifetime	60'000h
Working T°	-30°C ~ +55°C
Option	AGC: Anti Glare Optic



#### Color Temperature & Luminous Flux / Unit

CCT	<b>2800K</b>	<b>4000K</b>
Luminous Flux/Unit	40 lm	45 lm

#### CERTIFICAT

